300Mbps WALL-PENETRATING WIRELESS ROUTER





Model No. RNH326

3*5dbi high gain omni-directional antennas: 3*5dbi high gain omni-directional antennas with 300M wireless transmission rate ensure stable WiFi with WiFi coverage up to 300m.

Install in one step

Simple and easy installation guide let you access internet as you please.

Bandwidth control

IP-based broadband control allows you to distribute bandwidth to specific PCs.


High-level wireless security

Supports advanced wireless encryption mechanism like WPA-PSK, WPA2-PSK, WPA/WPA2 etc, effectively anti-rub network.

BROADOM.

Adopts Broadcom chip to bring terrific performance

Adopts American Broadcom chip same as Apple devices to bring terrific performance with ultra-fast data processing & stable wireless transmission.



WiFi timer switch ensures greenlumi

WiFi timer switch lets you enjoy a greenlumi and healthy e-life.



WiFi coverage is up to 300m²

3*5dbi high gain omni-directional antennas with 300M wireless transmission rate ensure stable WiFi with WiFi coverage up to 300m².

300Mbps WALL-PENETRATING WIRELESS ROUTER



Sanscord RNH326 is a Wi-Fi router specially designed for Home, office users by Ramptel Solutions Private Limited. It is Adopting American Broadcom Wi-Fi chip which is the same as Apple devices, it boasts highly steady performance and is compatible with all smart phones, iPads and PCs, thus, you can surf the Internet smoothly. Three external 5dBi high-gain omni-directional antennas, based on signal amplifier technology and powerful wall penetrating ability, can bring you free and easy enjoyment of Internet access. By using RNH326 High Power Router , there will be no black spots and user can get Wi-Fi coverage every where. What's more, it's very easy for you to install RNH326 by simply following the latest easy-installation setup. Energy-saving, environmental-friendly WiFi ON/OFF timer function lets you enjoy the fashionable, green and healthy e-life.

- · · · / · · · · ·	
HARDWARE FEATURES	
Protocols & standards	IEEE802.11/b/g/n
Interface	1*10/100M auto-negotiation WAN port 3*10/100M auto-negotiation LAN portsb
Antennas	3*5dBi external antennas
Transmission rate	300Mbps
LED Indicator	SYS, WLAN, LAN3, LAN2, LAN1, WAN
Button	1*RESET/WIFI button
Power Input	100-240V—50/60Hz 0.3A
Power Output	DC 9V==0.6A
Dimension / Weight	15.5(L) x 28.8(W) x 2.5(H) cm/ 300gms
SOFTWARE FEATURES	
WAN Connection Type	PPPoE, Dynamic IP; Static IP
Operating Mode	Router mode, WISP, Universal Repeater
VPN Pass-through	Support
Other Functions	Bandwidth control, Smart WiFi Schedule, MAC clone, upgradeable Web software
Wireless Features	
Wireless Security	WPA-PSK/WPA2-PSK、WPA、WPA2
Frequency	2.4~2.4835 GHz
OTHERS	
Temperature	Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C
Humidity	Operating Humidity: 10%~90% RH non-condensing
·	Storage Humidity: 5%~90% RH non-condensing Windows 2000 with latest upgrades
Ou a wati a w Couat awa	. •
Operation System	IE5.0 or Firefox1.0 with latest upgrades Network card has been installed
Default Settings	Password: admin IP address: 192.168.1.1
Certification	CCC、CE、RoHs
Packing Accessories	1* Router, 1* Power Adapter, 1*Quick Installation Guide, 1* Etherent Cable
acking Accessories	1 Notice, 1 Tower Adapter, 1 Quick Installation Guide, 1 Etherent Cable



Contact Us:

Ramptel Solutions Private Limited B-50, Sector-64, Noida 201007, U.P.

Tel. No. 120-4242072, Mobile: 9910212757 / 99102128333 E-mail: sales@ramptel.com, Website: www.ramptel.com